

PRE-INSTALLATION CHECKLIST

VERSION 5 – August 2023

This checklist should be completed by the customer to confirm on-site requirements are set for successful installation of the PATsmart™ REBEL® System. Please return the completed form to your Repligen contact. Questions? Just ask us at TechSupport@repligen.com.

CUSTOMER INFORMATION

Name of company / site

Address of site

Name of primary contact

Phone #

Email

Name of secondary contact

Phone #

Email

Details for focused training & support...

What is the primary application?

Any secondary application(s)?

Typical media in your lab? (check all that apply and/or provide specifics under 'other')

- Basal media (example: DMEM)
- CHO
- HEK293
- Fermentation (yeast, microbial)
- Insect
- T-cell
- MSC
- Other

Any relevant commercial media?

PRE-INSTALLATION '10 POINT' CHECKLIST

- 1 The primary operator(s) of the device will be on site and available during the installation of hardware and training.
- 2 A bench or cart space is available to support the Rebel measuring at least (22 in (h) x 13 in (w) x 27 in (d)) and weighing 38 kg (83 lbs).
- 3 There is one (1) electrical power receptacle (100-240VAC / 50-60Hz) available within 2 m (6 ft) of back of the REBEL system.
- 4 There is a waste stream available for disposal of REBEL aqueous waste.
- 5 IT personnel will be available during installation for setup of REBEL networking. Refer to 'Network Configuration' for further details.
- 6 The laboratory environmental temperature is maintained in the range of 20 – 25°C (68-77°F).
- 7 The laboratory relative humidity is 20-80% non-condensing.
- 8 The laboratory atmosphere is clean, free of smoke/fumes, excess dust and volatile chemical background contamination (e.g: acetonitrile, alcohols, ketones).
- 9 Upon receipt of the REBEL and IQOQ consumables kit (P/N 850-00059), the standards pouch will be refrigerated (2-8°C), and the system will remain in the original packaging.
- 10 Basic laboratory supplies for use with the REBEL are available during installation and training including gloves, lint-free cleanroom wipes (e.g. Texwipes), 2 mL vials and/or microwell plates, pipettes/tips, high purity isopropyl alcohol, and compressed air source (example: keyboard duster, benchtop connection).

REBEL SPECIFICATIONS

Physical	height (22 in, 56 cm), width (13 in, 33 cm), depth (27 in, 69 cm)
Weight	83 lbs (38 kg)
Power	100-240AC, 50-60 Hz
Ambient Operating Temperature	20°C - 25°C (68-77°F)
Ambient Humidity	20-80% RH (non-condensing)



NETWORK CONFIGURATION

- REBEL is an embedded system running a captive application on a background Windows Pro 10 OS.
- The system can run stand-alone or on a network (ethernet) connection.
- No external internet connection is required.
- **NOTE:** Local data storage should be considered **impermanent** – the Rebel has limited internal storage and will delete data/reports on a first-in-first-out basis when its disk is nearly full. It is *strongly* recommended that a **network storage** location for data retention/protection purposes be configured in cGMP/cGLP environments.

Network Configurations	Storage Configurations
<ol style="list-style-type: none"> 1. None – run standalone with USB-only data access 2. Static IP 3. DHCP 	<ol style="list-style-type: none"> 1. Local storage – considered temporary for 21CFRpt11 purposes 2. Network storage

Network Configs

Use DHCP

IP Address:

Netmask: 255.255.255.0

Gateway: 192.168.1.1

DNS Server 1: 8.8.8.8

DNS Server 2: 192.168.1.53

APPLY

Local storage

Export Formats

CSV reports

PDF reports

TEL (raw) data files

Storage Location

Internal storage should be considered temporary for record retention purposes

Network storage

Export Formats

CSV reports

PDF reports


TEL (raw) data files

Storage Location

Write location (UNC): \\host-name\my_writeshare\

Read location (UNC): \\host-name\my_readshare\

Test permissions



REPLIGEN CONTACTS

Please contact us if you need any help or support prior to the install:

Repligen Corporation

685 Route 202/206

Bridgewater, NJ 08807, USA

www.repligen.com

TECH SUPPORT: TechSupport@repligen.com

SALES SUPPORT: analytics-sales@repligen.com

1-888-927-3035

LAST STEP...

All pre-installation checklist items are done, and we are ready to receive the REBEL.

CUSTOMER SIGNATURE _____

DATE _____